

DS型磁心 DS Cores




图1 Fig.1




图2 Fig.2



产品型号 Type	图号 Fig	尺寸 Dimensions (mm)						
		A	B	C	D	E	F	G
DS30/8.3/20F	1	30.0±0.5	8.3±0.1	20.3±0.3	13.3±0.2	25.1min	5.6±0.2	18.8min
DS30/9.4/20F	1	30.0±0.5	9.4±0.2	20.25±0.35	13.2±0.2	25.0min	6.6±0.2	17.5min
DS31/8.3/20F	1	31.0±0.5	8.3±0.2	20.25±0.35	13.2±0.2	25.7min	5.6±0.2	18.5min
DS31/9.4/20F	1	31.0±0.5	9.4±0.2	20.25±0.35	13.2±0.2	25.7min	6.6±0.2	18.5min
DS33/9.4/24F	1	33.2±0.5	9.4±0.2	23.7±0.3	13.5±0.2	26.0min	6.5±0.2	18.8min
DS33/12.7/24F	1	33.2±0.5	12.7±0.2	23.7±0.3	13.5±0.2	26.0min	9.7±0.2	18.8min
DS34/9.5/24F	1	34.0±0.5	9.5±0.2	24.0±0.3	13.6±0.2	27.5min	6.65±0.2	20.4min
DS40/7.7/28F	2	39.8±0.5	7.7±0.2	28.3±0.4	16.0±0.25	32.7min	4.75±0.2	21.8min
DS40/11.1/28F	1	39.8±0.5	11.1±0.2	28.3±0.35	16.0±0.25	32.7min	7.5±0.2	20.0min
DS40/13.5/28F	1	39.8±0.5	13.5±0.2	28.3±0.4	16.0±0.25	32.7min	9.9±0.2	20.0min

产品型号 Type	磁心参数 Core parameter				AL(nH/N ²)				重量 weight (g/prs)
	C1 (mm ⁻¹)	Le (mm)	Ae (mm ²)	Ve (mm ³)	ACP40 (±25%)	ACP44 (±25%)	ACP47 (±25%)	ACP95 (±25%)	
DS30/8.3/20F	0.37	44.63	121	5400	5800	5800	5800	6960	27.8
DS30/9.4/20F	0.37	48.33	118.74	5739.7	5500	5500	5500	6600	29.6
DS31/8.3/20F	0.36	45.08	124	5590	5800	5800	5800	6960	28.8
DS31/9.4/20F	0.39	49.12	124.4	6110	5500	5500	5500	6600	31.5
DS33/9.4/24F	0.39	49.12	147	7400	5500	5500	5500	6600	38.1
DS33/12.7/24F	0.39	60.75	156.87	9530	5800	5800	5800	6960	49.1
DS34/9.5/24F	0.39	50.63	149.7	7579.6	6000	6000	6000	7200	39.0
DS40/7.7/28F	0.24	44.3	187	8284	7500	7500	7500	9000	42.7
DS40/11.1/28F	0.28	59.48	211.04	12552	7800	7800	7800	9360	64.6
DS40/13.5/28F	0.31	68.13	213.32	14532.6	6600	6600	6600	7920	74.8