

T型磁心 T Cores




图1 Fig.1




图2 Fig.2



产品型号 Type	图号 FIG	尺寸 Dimensions (mm)		
		A	B	C
T6/3/3	1	6.0±0.3	3.0±0.3	3.0±0.3
T8/4/4	1	8.0±0.3	4.0±0.3	4.0±0.3
T9/5/3	1	9.0±0.3	5.0±0.3	3.0±0.3
T10/6/5	1	10.0±0.4	6.0±0.4	5.0±0.3
T12/6/4	1	12.0±0.4	6.0±0.4	4.0±0.3
T14/7/7	1	14.0±0.5	7.0±0.5	7.0±0.3
T14/9/5	1	14.0±0.5	9.0±0.5	5.0±0.3
T16/12/8	1	16.0±0.4	12.0±0.3	8.0±0.3
T18/10/7	1	18.0±0.5	10.0±0.5	7.0±0.3
T18/10/7G	2	18.0±0.5	10.0±0.5	7.0±0.3
T18/10/10	1	18.0±0.5	10.0±0.5	10.0±0.3
T20/12/10	1	20.0±0.5	12.0±0.5	10.0±0.3
T20/12/10G	2	20.0±0.5	12.0±0.5	10.0±0.3
T22/14/8	1	22.0±0.6	14.0±0.6	8.0±0.3
T22/14/8G	2	22.0±0.6	14.0±0.6	8.0±0.3
T25/15/10	1	25.0±0.4	15.0±0.4	10.0±0.3
T25/15/12	1	25.0±0.6	15.0±0.6	12.0±0.3
T31/19/13	1	31.0±0.6	19.0±0.6	13.0±0.3
T36/23/15	1	36.0±0.7	23.0±0.5	15.0±0.3



T型磁心 T Cores

产品型号 Type	磁心参数 Core parameter				AL(nH/N ²)				重量 weight g/pcs
	C1 (mm ⁻¹)	Le (mm)	Ae (mm ²)	Ve (mm ³)	ACH5K (±25%)	ACH7K (±25%)	ACH10K (±30%)	ACH12K (±30%)	
T6/3/3	3.05	13.1	4.3	56.3	2000	2700	2900min	4500	0.3
T8/4/4	2.26	17.4	7.7	134.0	2700	3600	5800	6100	0.8
T9/5/3	3.59	20.8	5.8	120.6	1700	2200-5900	2900min	3800	0.7
T10/6/5	2.54	25.4	10	254.4	2400min	3200	4900	5400	1.4
T12/6/4	2.27	26.1	11.5	300.2	2800	3600	6500	6000	1.7
T14/7/7	1.30	30.5	23.54	717.7	4800	6300	8000min	10500	3.9
T14/9/5	2.84	35.0	12.3	430.3	2200	2900	3480min	4800	2.4
T16/12/8	2.73	43.4	15.9	690.1	2300	3000	4000min	6500	3.4
T18/10/7	1.53	41.5	27.2	1128.8	4100	6000min	8000	9600	5.7
T18/10/7G	1.53	41.5	27.2	1128.8	4100	6000min	7100min	9600	5.8
T18/10/10	1.07	41.5	38.9	1614.4	5900	7600	11800	12900	8.2
T20/12/10	1.23	48.1	39.14	1884.2	5100	6600	10000	11000	10.4
T20/12/10G	1.23	48.1	39.14	1884.2	5100	6600	10000	11000	10.5
T22/14/8	1.74	54.7	31.5	1723.1	3600	4700	7200	7900	9.5
T22/14/8G	1.74	54.7	31.5	1723.1	3600	4700	7400	7900	9.5
T25/15/10	1.17	60.6	51.8	3139.1	5400	7000	10000	11800	15.3
T25/15/12	0.94	59.7	63.2	3773.0	6600	7000min	12000	14600	18.9
T31/19/13	0.99	75.5	76.5	5775.8	6400	8300	12480	14000	29.0
T36/23/15	0.95	89.7	94.1	8440.8	6600	8600	13000	14500	45.2